

## XPS-052T1

4 port 10/100 PoE + 1 port 10/100TX Uplink Unmanaged Switch - Built-in Power Supply



- 4 Port 10/100 PoE
- 1 Port 10/100 Megabit Uplink
- Total PoE Budget: 65W
- IEEE802.3x

### Technical Specs.

Model No	XPS-052T1
Port Capacity	5 Port Megabit Unmanaged Switch
Port Types	4 port 10/100Base-TX RJ45 copper ports (PoE) + 1 port 10/100 RJ45 copper port

### Performance

Switching Capacity	1 Gbps (non-blocking)
Forwarding Rate	0.74 Mpps
MAC Table	1K

### Features

Switch Architecture, Store-and-Forward	Auto MDI/MDIX
IEEE 802.3	Auto Negotiation
IEEE 802.3i	IEEE 802.3af
IEEE 802.3u	
IEEE 802.3x	

### PoE

Standard	IEEE802.3af
Total PoE Budget	65 W
Max. PoE Power for each port	15.4 W

### Environment

Input Power	AC100-240V 50-60Hz
Total Power Consumption	76 W
Operating/Storage Temperature	0 - 50 °C / -20 - 75 °C
Operating Humidity	10% - 90%, non-condensing

### Mechanical

Dimension	185 x 113 x 36 mm
Weight	0.609 kg
Installation	Free-standing, wall-mounted

### Standards and Protocols

CE	RoHS
FCC Class A	ISO 9001

### Ordering Information

<b>XPS-052T1</b>	4 port 10/100 PoE + 1 port 10/100TX Uplink Unmanaged Switch - Built-in Power Supply
------------------	-------------------------------------------------------------------------------------