

## XPS-I7100-6P

4 port 10/100/1000 PoE + 2 port 100/1000 SFP Unmanaged Industrial Switch



- 4 Port 10/100/1000BaseT
- 2 Port 100/1000 SFP
- Total PoE Budget: 120 W
- 4 ports PoE
- IEEE802.3x
- Auto Negotiation
- Store-and-Forward

### Technical Specs.

<b>Model No</b>	XPS-I7100-6P
<b>Port Types</b>	4 port 10/100/1000Base-T RJ45 copper ports (PoE) + 2 port 100/1000 SFP

### Performance

<b>Switching Capacity</b>	12 Gbps, wire speed, (non-blocking)
<b>Forwarding Rate</b>	8.93 Mpps
<b>MAC Table</b>	16K

### Features

IEEE 802.3	IEEE 802.3x
IEEE 802.3i	Auto MDI/MDIX
IEEE 802.3u	Auto Negotiation
IEEE 802.3ab	Store-and-Forward
IEEE 802.3z	

### PoE

<b>Standard</b>	IEEE802.3af IEEE802.3at
<b>Total PoE Budget</b>	120W
<b>Max. PoE Power for each port</b>	30W

### Environment

<b>DC Power Input</b>	47-55V
<b>Total Power Consumption</b>	67W
<b>Operating/Storage Temperature</b>	-40 - 75 °C / -50 - 85 °C
<b>Operating Humidity</b>	5% - 95% , non-condensing

### Mechanical

<b>Dimension</b>	128 x 100 x 54 mm
<b>Weight</b>	0.565 kg
<b>Installation</b>	IP40 rating , DIN-rail

### Standards and Protocols

EN55022	EN61000-6-2	EN61000-4-5	IEC60068-2-27 Ea
EN61000-6-4	EN61000-4-2	EN61000-4-6	CE
EN61000-3-2	EN61000-4-3	EN61000-4-8	FCC
EN61000-3-3	EN61000-4-4	IEC60068-2-6	ISO 9001

### Ordering Information

<b>XPS-I7100-6P</b>	4 port 10/100/1000 PoE + 2 port 100/1000 SFP Unmanaged Industrial Switch
---------------------	--

### Modules

<b>XPS-I21LX</b>	XPS Industrial Dual Core LX SM 10Km SFP Module -40/75°C
<b>XPS-I21SX</b>	XPS Industrial Dual Core SX MM SFP Module -40/75°C

\*more module ranges are available upon request.