

XPS-PEBTAT4

1 port 1000T 90W PoE++ In + 4 port 1000T 30W PoE+ Out Industrial Poe Extender



- 5 Port 1000BaseT
- 1 Port 802.3af/at/bt POE In PD
- 4 Port 802.3af/at POE Out PSE
- IP30
- Industrial Grade

Technical Specs.

Model No	XPS-PEBTAT4
Port Capacity	5 Port 10/100/1000BaseT
Port Types	1 port 1000T 90W PoE++ In PD + 4 port 1000T 30W PoE+ Out PSE Industrial Poe Extender

Performance

Switching Capacity	10 Gbps , wire speed (non-blocking)
Forwarding Rate	7.44 Mpps
MAC Table	8K
Memory	2M
Auto-negotiation	✓
Auto MDI/MDIX	✓
Store-and-Forward	✓

PoE

Standard	IEEE802.3af IEEE802.3at IEEE802.3bt
Total Power Budget	90W
Max. PoE Power for each port	4 PSE port 30W each

Environment

DC Power Input	DC 47-55V or 802.3af/at/bt PSE source
Total Power Consumption	Max . 95W DC
Operating/Storage Temperature	-40 - 75 °C / -50 - 85 °C
Operating Humidity	5% - 95% , non-condensing
MTBF	> 255.000 hours

Mechanical

Dimension	139 x 80 x 27 mm
Weight	0.3 kg
Installation	IP30 rating

Standards ETSI CE FCC IEC ISO SELV

EN55022	EN61000-6-2	EN300019-1-4	CISPR22
NEC Class 2	EN61000-4-2	EN61000-4-6	IEC60950-1
EN61000-3-2	ITU-T K.45	IEC60950-22	FCC CFR 47
EN61000-3-3	EN300386	IEC60068-2-6	ISO 9001

Ordering Information

XPS-PEBTAT4	1 port 1000T 90W PoE In + 4 port 1000T 30W PoE Out Industrial Poe Extender
--------------------	--