


XPS-1100-26

24 port 10/100TX + 2 port 100/1000 SFP Unmanaged Switch



- 24 Port 10/100BaseTX
- 2 Port 100/1000 SFP
- IEEE802.3x
- Auto Negotiation
- Store-and-Forward

Technical Specs.

Model No	XPS-1100-26
Port Types	24 port 10/100Base-TX RJ45 copper ports + 2 port 100/1000 SFP

Performance

Switching Capacity	8.8 Gbps
Forwarding Rate	6.55 Mpps
MAC Table	16K

Features

IEEE 802.3	IEEE 802.3x
IEEE 802.3i	Auto MDI/MDIX
IEEE 802.3u	Auto Negotiation
IEEE 802.3ab	Store-and-Forward
IEEE 802.3z	

Environment

Input Power	AC100-240V, 1A, 50-60Hz
Total Power Consumption	20 W
Operating/Storage Temperature	0 - 50 °C / -20 - 75 °C
Operating Humidity	10% - 90%, non-condensing

Mechanical

Dimension	440 x 225 x 44 mm
Weight	1.530 kg
Installation	Free-standing, wall mounted

Standards and Protocols

CE	RoHS
FCC	ISO 9001

Ordering Information

XPS-1100-26	24 port 10/100TX + 2 port 100/1000 SFP Unmanaged Switch
--------------------	---

Modules

XPS-21LX	XPS Dual Core LX SM 10Km SFP Module -10/50°C
XPS-21SX	XPS Dual Core SX MM SFP Module -10/50°C

*more module ranges are available upon request.