

## XPS-I7120-10

8 port 10/100/1000T + 2 port 100/1000 SFP L2+ Managed Industrial Switch



- 8 Port 1000BaseT
- 2 Port 100/1000 SFP
- L2+ Features
- IEEE802.1x
- IEEE802.3az
- IEEE802.3z/ab
- IP30
- DIN Rail

### Technical Specs.

<b>Model No</b>	XPS-I7120-10
<b>Port Capacity</b>	10 Port Industrial Managed Switch
<b>Port Types</b>	8x 10/100/1000Base-T RJ45 copper ports + 2x 100/1000 SFP ports + 1 RJ45 console port

### Performance

<b>Switching Capacity</b>	20 Gbps, wire speed (non-blocking)
<b>Forwarding Rate</b>	14.88 Mpps
<b>MAC Table</b>	8K
<b>Jumbo Frames</b>	9.6K
<b>Memory</b>	4M
<b>Auto-negotiation</b>	•
<b>Auto MDI/MDIX</b>	•
<b>Store-and-Forward</b>	•

### Layer 2+ Features

<b>Spanning Tree Protocol (STP)</b>	IEEE802.1d Spanning Tree Protocol IEEE802.1w Rapid Spanning Tree Protocol IEEE802.1s Multiple Spanning Tree Protocol Loop Back Detection
<b>IGMP Snooping</b>	IGMP v1/v2
<b>VLANs</b>	Support up to 4K VLANs Port-based VLAN 802.1Q tag-based VLAN
<b>Link Aggregation</b>	IEEE 802.3ad LACP
<b>Ethernet Ring Protection Switching</b>	G.8032 ERPS
<b>Flow Control</b>	IEEE802.3x
<b>Private VLAN</b>	•
<b>Static Routing</b>	•
<b>Q in Q</b>	•

### Security Features

<p><b>Broadcast, multicast , unicast storm control</b>  <b>Secure Sockets Layer (SSL), Web security</b>  <b>DHCP Snooping</b>  <b>ARP Inspection</b>  <b>IP Source Guard</b>  <b>AAA, RADIUS and TACACS+</b></p>	<p><b>Secure Shell (SSH), Telnet security, supports SSH v1 and v2</b>  <b>ACL, VLAN ID or IP address,</b>  <b>MAC Based, Protocol based, Port Based, TCP/ UDP</b>  <b>Ethernet type,ICMP, IGMP, TCP flag</b>  <b>Port Security</b></p>
--	--

### Management

Web/SSL	SNMP	Firmware upgrade,
Port Mirroring	DHCP Client	(HTTP/HTTPs and TFTP)
Port Isolation	Web GUI Interface	LLDP
Telnet/SSH	Cable Diagnostics	SNTP
Ping	CPU Load	TFTP
HTTP/HTTPs	Dual Image	Syslog
Timezone		

### IPv6

IPv6 MLD snooping	IPv4/IPv6 Dual Protocol Stack
IPv6 Ping	

### Quality of Service

<b>CoS</b>	8 queues per port TCP/ UDP Strict priority Weighted Round Robin (WRR)
<b>Rate Limiting</b>	Ingress/Egress Rate control
<b>Traffic classification</b>	IEEE802.1p DSCP / IP precedence

### Environment

<b>DC Power Input</b>	12-48V
<b>Total Power Consumption</b>	12.2W
<b>Operating/Storage Temperature</b>	-40 - 75 °C / -50 - 85 °C
<b>Operating Humidity</b>	5% - 95% , non-condensing

**Mechanical**

<b>Dimension</b>	165 x 148 x 54 mm
<b>Weight</b>	0.885 kg
<b>Installation</b>	IP30 rating , DIN-rail

**Standards**

EN55022	EN61000-4-4	EN61000-6-4	CE
EN61000-3-2	EN61000-4-5	IEC60068-2-6	FCC
EN61000-3-3	EN61000-4-6	IEC60068-2-27 Ea	RoHS
EN61000-4-2	EN61000-4-8	CE/LVD EN60950	ISO 9001
EN61000-4-3	EN61000-6-2	VCCI Class B	

**Ordering Information**

**XPS-I7120-10**      8 port 10/100/1000T + 2 port 100/1000 SFP L2+ Managed Industrial Switch

**Modules**

**XPS-I21LX**      XPS Industrial Dual Core LX SM 10Km SFP Module -40/75°C

**XPS-I21SX**      XPS Industrial Dual Core SX MM SFP Module -40/75°C

\*more module ranges are available upon request.