

XPS-PEATAT2

1 port 1000T 30W PoE In + 2 port 1000T 30W PoE Out Industrial Poe Extender



- 3 Port 1000BaseT
- 1 Port 802.3af/at POE In PD
- 2 Port 802.3af/at POE Out PSE
- IP30
- Industrial Grade

Technical Specs.

Model No	XPS-PEATAT2
Port Capacity	3 Port 10/100/1000BaseT
Port Types	1 port 1000T 30W PoE In PD + 2 port 1000T 30W PoE Out PSE Industrial Poe Extender

Performance

Switching Capacity	6 Gbps , wire speed (non-blocking)
Forwarding Rate	4,46 Mpps
MAC Table	8K
Memory	1M
Auto-negotiation	✓
Auto MDI/MDIX	✓
Store-and-Forward	✓

PoE

Standard	IEEE802.3af IEEE802.3at
Total Power Budget	30W
Max. PoE Power for each port	2 PSE port 30W each (total budget 30W)

Environment

DC Power Input	DC 47-55V or 802.3af/at PSE source
Total Power Consumption	Max . 35W DC
Operating/Storage Temperature	-40 - 75 °C / -50 - 85 °C
Operating Humidity	5% - 95% , non-condensing
MTBF	> 255.000 hours

Mechanical

Dimension	85 x 82,5 x 20 mm
Weight	0.1 kg
Installation	IP30 rating

Standards ETSI CE FCC IEC ISO SELV

EN55022	EN61000-6-2	EN300019-1-4	CISPR22
NEC Class 2	EN61000-4-2	EN61000-4-6	IEC60950-1
EN61000-3-2	ITU-T K.45	IEC60950-22	FCC CFR 47
EN61000-3-3	EN300386	IEC60068-2-6	ISO 9001

Ordering Information

XPS-PEATAT2	1 port 1000T 30W PoE In + 2 port 1000T 30W PoE Out Industrial Poe Extender
--------------------	--