

### Product Description:

- T110
- Hard plastic covers on top of each PCB to refrain from incidental damage
- Higher Printed-circuited board capacity
- Color-coded for T568A and T568B wiring schemes

### Physical Specifications

- High-density 1U, 19" Rack Mount Standard 24 ports design
- Apply UL 94V high-impact, fire-retardant ABS material
- A pair punch sequence enables a pair twist within 1/2" of termination
- IDE:22-26 AWG wires
- Beryllium copper contact: 50- $\mu$ " gold-plated pins over 100- $\mu$ " nickel layer
- Insertion life cycle:1000 cycles (min.)/ I.D.C. 250 cycles (min.)
- Operating temperature:-40°C to +68°C.
- Color: Black

### Electrical Characteristics

- Insulation Resistance : 500M.
- Contact Resistance : 20M.
- Current rating : 1.5 Amps
- DC Resistance : Max. 0.1
- Dielectric withstand V: 1,000 VAC RMS @ 60 Hz/1 min.

### Applications

- 10 BaseT, 100BaseTX, 1000BaseT
- 4-16Mbit Token Ring
- 622-155Mbit ATM
- ISDN
- Analog Voice

### Standards

- EIA/TIA568.B2.1
- ISO 11801 2nd. Version
- EN 50173-1



Ordering Information:

Part No:  
PP-C6-U-24

Description:

XPcable CAT6 UTP 24 Port Patch panel



**ELECTRONICS CO., LTD.**

RM A206, 11FL., No. 51 Hengyang Road, Taipei 100, Taiwan, R.O.C.

[www.xpcable.com](http://www.xpcable.com)