

## XPS-330X

2 Port 10/100TX to 100FX SM/MM F/O Media Converter



- 2x 10/100BaseTX
- 100BaseFX
- Auto MDI/MDIX
- IEEE802.3x, Flow Control
- LFPT

**Technical Specs.**

Model No	XPS-330DF
Port Types	2 port RJ45 copper port + 1 Fiber SC Port

**Performance**

Wavelength	850-1310 nm
Fiber Bandwidth	200 Mbps

**Features**

IEEE 802.3i	Auto Negotiation
IEEE 802.3u	Link Fault Pass Through
IEEE 802.3x	Store and Forward

**Environment**

Power Consumption	2.20W, max. 12VDC
Operating/Storage Temperature	0 - 50 °C / -20 - 75 °C
Operating Humidity	10% - 90%, non-condensing

**Mechanical**

Dimension	116 x 114 x 25.5 mm
Weight	0.75 kg
Installation	Free-standing, wall-mounted

**Standards and Protocols**

CE mark, commercial	VCCI Class B
FCC Part 15 Class B	EN 55022 (CISPR 22), Class B
CE/LVD EN60950	ISO 9001

**Ordering Information**

<b>XPS-330M</b>	2 port 10/100TX to 100FX MM SC Dual Fiber Converter 850nm
<b>XPS-330S</b>	2 port 10/100TX to 100FX SM SC Dual Fiber Converter 20Km 1310nm