

XPS-I7100-4

2 port 10/100/1000T + 2 port 100/1000 SFP Unmanaged Industrial Switch



- 2 Port 10/100/1000BaseT
- 2 Port 100/1000 SFP
- IEEE802.3x
- Auto Negotiation
- Store-and-Forward

Technical Specs.

Model No	XPS-I7100-4
Port Types	2 port 10/100/1000Base-T RJ45 copper ports + 2 port 100/1000 SFP

Performance

Switching Capacity	8 Gbps, wire speed (non-blocking)
Forwarding Rate	5.95 Mpps
MAC Table	16K

Features

IEEE 802.3	IEEE 802.3x
IEEE 802.3i	Auto MDI/MDIX
IEEE 802.3u	Auto Negotiation
IEEE 802.3ab	Store-and-Forward
IEEE 802.3z	

Environment

DC Power Input	12-48V
Total Power Consumption	6.1W
Operating/Storage Temperature	-40 - 75 °C / -50 - 85 °C
Operating Humidity	5% - 95% , non-condensing

Mechanical

Dimension	110 x 80 x 43 mm
Weight	0.390 kg
Installation	IP40 rating , DIN-rail

Standards and Protocols

EN55022	EN61000-6-2	EN61000-4-5	IEC60068-2-27 Ea
EN61000-6-4	EN61000-4-2	EN61000-4-6	CE
EN61000-3-2	EN61000-4-3	EN61000-4-8	FCC
EN61000-3-3	EN61000-4-4	IEC60068-2-6	ISO 9001

Ordering Information

XPS-I7100-4	2 port 10/100/1000T + 2 port 100/1000 SFP Unmanaged Industrial Switch
--------------------	---

Modules

XPS-I21LX	XPS Industrial Dual Core LX SM 10Km SFP Module -40/75°C
XPS-I21SX	XPS Industrial Dual Core SX MM SFP Module -40/75°C

*more module ranges are available upon request.